

June, 2020

3M™ Performance Yellow Masking Tape 301+

Product Description

3M™ Performance Yellow Masking Tape 301+ is a general purpose industrial paint masking tape. For vehicle masking it is designed for less critical paint lines and paper holding. It also is used for architectural and MRO painting. It is a conformable crepe paper tape that is easy to apply, and to remove in one piece. Bake temperature resistance is up to 225°F (107°C) tor 30 minutes.



Product Features

- Creates good paint lines and resists edge bleed by most industrial paints.
- Removes cleanly, as adhesive and backing resist leaving residue and slivering.
- Easy to unwind and easy to apply.
- Sticks instantly to many surfaces. The 3M proprietary solvent free adhesive is designed to hold in place, and to remove more easily than some thicker tapes.
- Highly visible yellow crepe-paper backing conforms around curves and contours.
- Prolonged outdoor exposure may make tape difficult to remove.

3M™ Performance Yellow Masking Tape 301+

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Yellow		
Total Tape Thickness	0.14 mm	5.4 mil	ASTM D3652
Backing	Smooth crepe paper		
Adhesive	Rubber		

Typical Performance Characteristics

Property	Values		Method	Dwell/Cure Time	Substrate	Notes
180° Peel Adhesion	3.6 N/cm	33 oz/in	ASTM D3330	Initial	Stainless Steel	12 in/min (300 mm/min)
Tensile Strength	35 N/cm	20 lb/in	ASTM D3759			
Elongation at Break	n 11 %		ASTM D3759			
Temperat Use Range	u&O minutes up to 107 °C	30 minutes up to 225 °F				

Available Sizes

Property	Values	
Standard Roll Length	55 m	60 yd

Storage and Shelf Life

Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton. To obtain best performance, use within 18 months from date of manufacture.

Trademarks

3M is a trademark of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all- 3m-products/~/3M-Performance-Yellow-Masking- Tape-301?N=5002385+3293193658&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/? gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=301

ISO Statement

This Closure and Masking Systems Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Performance Yellow Masking Tape 301+

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



