

G-B1222-1330

Protective glue

Brief introduction

G-B1222-1330 is design specifically for the laser cutting process. Perfectly suitable for lasercutting that improves the lubricity while improving of coolant created by cutting process.

Product advantages

Reduces heating and burning during laser cutting.

Decrease the sum up of particles from sticking as well as particle removal.

To provide a coating protection for wafers.

To provide a debris free quality during the dicing process.

A fully water soluble synthetic polymer.

Completely suitable for the laser cutting technology today.

Recommended Handling Conditions

Protect from freezing

Keep container tightly closed

Shelf Life: 1 year

Storage at 25±10°C

Physical Properties

Appearance and Order	Clear liquid
PH	6-8
Viscosity	300-500 cP (@25°C)
Solubility in Water	Soluble
Hardness (Shore D)	55
Surface dry (20µm)	5 min
Shear strength Glass/Glass	0.7 MPa

Note:

1. Keep this product away from children.
2. It is recommended to use this product in a well ventilated area.
3. If it accidentally gets on the skin, please wash it immediately with soap and water.
4. If it accidentally enters the eyes, please rinse with plenty of water first and then seek medical attention.

Contact information

Company:
ICM Industrial development CO., LTD

Address:
7F. Xi angyu centre No1588 Entrepreneurial Road, Kunshan Ci ty, Ji angsu, Chi na

Tel ephone: 0512 - 57377066

Websi te: [www. icmrop. com](http://www.icmrop.com)